#### **UA9 Thin Client**

Workforce Mobility Simplified







### **Built Durable, Built for the Mobile Workforce**

The fanless UA9 eliminates moving components, ensuring unmatched durability and dependability for your mobile workforce



#### **Stay Connected, Stay Productive**

Built-in WiFi, wired connectivity, and support for two UHD/4K displays create a seamless, immersive workspace for mobile teams



## Efficiency that Saves the Day—and Your Budget

Equipped with the Intel® Alder Lake CPU, UA9 slashes electricity costs, reduces e-waste, and extends its operational lifespan—all while delivering exceptional performance



#### Big Screen, Big Results

UA9's 15.6-inch LCD screen and Numpad keyboard are designed for productivity, making it ideal for intensive mobile work environments

## **UA9 Thin Client**



Workforce Mobility Simplified

	Performance		Expo
СРИ	Intel® Alder Lake N100 processor supports up to 3.4GHz max boost frequency, Quad Core	WiFi	• Or int
Memory	8GB DDR4-3200MHz single channel		• M.:
Multiple Display	15.6" full HD LCD, 1 HDMI , USB-C	LAN	• Mi
Display Resolution	Full HD on LCD, 4K 60Hz on connected display (Max)	USB	3 USE
Brightness (typical)	250 cd/m² typ.		Comb
Viewing Angle	CR(>10):85/85 (V/H) typ.		Interr
Graphic & Multimedia	• Intel® 12th UHD Graphics 24EUs	Power	USB
	<ul> <li>Full HD 2MP webcam with microphone</li> <li>HEVC, VP9, and AVC decode</li> </ul>	Battery	Polyn Li-Po
	support  Support AVX2 instruction sets	Keyboard Language	Germ Dutcl

	Expandability	
WiFi	<ul> <li>Onboard combo WiFi6, 2 internal antenna (RTL8852BE)</li> <li>Bluetooth 5.2</li> </ul>	
Storage	<ul><li>M.2 2280 M Key 128GB SATA SSD</li><li>Micro SD Card Reader</li></ul>	
LAN	RJ-45 10/100/1000Mbps	
USB	3 USB-A 3.2 Gen1, 1 USB-C 3.2 Gen1 with DP Alt mode, power delivery	
Audio & Sound	Combo audio jack for headset & Internal speakers	
Power	USB Type-C 65W power adapter	
Battery	Polymer 3S1P 11.4V/3950mAh/45W Li-Polymer Battery, 3 cells	
Keyboard Language	German, Spanish, French, English, Dutch	

# Security | Manageability Security | Security lock 3\*7mm RJ45 LAN with standby power design supports Magic Packet wake-up event TPM | Infineon TPM 2.0

Cooling	Passive cooling (Noise-Free)	
Operating Temperature	0 °C to 35 °C, 32 °F to 95 °F	
Operating Humidity	20% - 80% non-condensing	

**Environment** 

Dimension (w x h x d) & Weight: 244 x 21.6 x 368mm / 1.8kg

Note: UltrArmor may update or modify information, products, or programs without prior notice.